

WYKAZ STALI ZBROJENIOWEJ

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
Nr	L [cm]	il. sztuk.	il. elem.	[kg/m]	Φ 6	Φ 8	Φ 8	Φ 10	Φ 12	Φ 16	Φ 20	Φ20			
GATUNEK STALI					A-0 (StOS)		A-III (34GS)					18G2 (S355)			
Stopa fundamentowa pełna St1 x 5 szt.															
1	120	5	5	0,888					26,6						
2	90	5	5	0,888					20,0						
3	135	6	5	0,888					36,0						
4	134	8	5	0,222	12,0										
Stopy niepełne na ławach x 3 szt. (trzony słupów)															
3	135	6	3	0,888					21,6						
4	134	8	3	0,222	7,2										
Stopa słupów szczytowych St2 x 2 szt.															
1	240	9	2	0,888					38,4						
2	190	9	2	0,888					30,4						
3	135	8	2	0,888					19,2						
4	174	8	2	0,222	6,2										
kotwy K	103	2	2	2,47								10,2			
Podwaliny pełne Pd L=30,85 m + 10% (na zakłady Lz)															
1	3085x1,10	8		0,617				167,5							
2	2x154	155		0,222	106,0										
Podwaliny obniżone Pdd L=13,20 m (+10% jw.)															
1	1320x1,10	8		0,617				71,7							
3	124+154	66		0,222	40,7										
Razem wg średnic				kg	172,1			239,2	192,2			10,2			
Razem wg gatunków				kg	172,1			431,4				10,2			
Ogółem				kg				613,7							